

UV / 平板打印机
Flatbed Printer

RB-1610

Color the world




- 3 pcs of DX8/4720 heads 三喷头, 打印快
- Auto height detection 自动测高
- Color-White-Varnish in one pass 白彩同打
- 160*100cm(63*39inches) 打印尺寸160*100cm(63*39英寸)



UV / 平板打印机 Flatbed Printer

RB-1610 UV

• Features 特点



Solid Guideways

7pcs of Hiwin linear guideways on X, Y and Z axis brings longer lifespan and more accurate positioning.

Z轴使用双方形导轨加丝杆导轨，承重性牢固性更好。



Control Panel

Emergency Stop button, along with other buttons bring convenient operation.


多功能控制面板，集成了紧急停止按钮。



Ball Screw

2pcs of thick ball screws on Z-axis combines with 2pcs of linear guideways makes sure of the fast and smooth movement.


Y轴两根加粗滚珠丝杆，搭配两根线性导轨，确保横梁移动又快又稳。



White Ink Stirring

The white ink stirring system avoids the precipitation. In addition, it is equipped with a low ink level alert system.


白墨搅拌系统避免白墨沉淀，另外配有缺墨报警器。



Vacuum Suction Platform

Vacuum suction table, solid enough to undertake 50kg weight. The blower is connected to enhance the suction force.

真空吸附平台，坚固耐用，50kg承重能力，连接鼓风机，吸力强劲。



Aluminum Rotary Device

The rotary device is made of full aluminum with an independent motor.

铝合金独立电机驱动的圆柱体工装可选。

• Specification 参数表

Model 型号		RB-1610
Printhead 喷头		Three DX8/XP600/4720 print heads
Resolution 分辨率		720*720dpi~720*2880dpi
Ink 墨水	Type 类型	UV curable hard/soft ink软硬墨可选
	Package size 包装	750ml /bottle
	Ink supply system 墨路系统	CISS Built Inside with Ink Bottle
	Consumption 消耗量	9-15ml/sqm
	Ink stirring system 白墨搅拌	Available已配置
Maximum printable area (W*D*H) 打印区域	Horizontal 平面	100*160cm(40*63inch;A1)
	Vertical 垂直	Substrate 25cm(10inches) /Rotary 8cm(3inches)
Media 介质	Type 类型	plastic, pvc, acrylic, glass, ceramic, metal, wood, leather, etc.相纸、胶片、布料、塑料、pvc、亚克力、玻璃、陶瓷、金属、木材、皮革等。
	Weight 重量	≤40kg
	Media (object) holding method 平台类型	Vacuum table
Software 软件	RIP 图像处理软件	Maintop6.1
	Control 控制软件	Wellprint
	Format 可接受格式	.tif/.jpg/.bmp/.gif/.tga/.psd/.psb/.ps/.eps/.pdf/.dcs/.ai/.eps/.svg
	System 操作系统	Windows XP/Win7/Win8/Win10
	Interface 数据接口	USB 3.0
	Language 语言	English/Chinese中英
Power 电力	Requirement 电力要求	50/60HZ 1000-1600W
	Consumption 功耗	1000W-1600W
Dimension 尺寸	Assembled 机器尺寸	280*166*138cm
	Operational 建议操作空间大小	292*182*122cm
Weight 重量		Net 530/ Gross 630 kg