

Direct to / 抖粉烫画机
Film Printer

Nova 60

Color the world



- 2 pcs of printheads 双喷头, 型号可选
- Tripple stages heating 三段式加热
- 700mm print size 70厘米打印尺寸
- Adjustable Suction Platform 可调吸风平台



Direct to / 抖粉烫画机 Film Printer

Nova 60

• Features 特点



Three-stage Heating

Separate control buttons for front, middle, and back heating with respective temperature display, making it convenient to monitor and control the heating process.

三段式加热，实时温度显示，方便观察控制。



Quality Pressure Roller

Extra-large pressure roller with increased friction brings better material rolling, making the paper feeding, printing, and taking-up more smoother.

重型压纸轮，让进纸更加稳定顺畅。



Reliable Circuit System

Hoson board, MW powder device, JMC motor, all of which are famous brands both in China and abroad with a large customer base.

可靠的板卡系统，重要部件进口，质量有保障。



Multifunction Panel

Multifunction control panel for cleaning, pause, nozzle test, menu, carriage movement, and paper feed and eject brings convenience for daily operation.

多功能面板，方便控制机器。



Large Ink Bottle

1L large capacity ink bottle reduces the frequency of manual ink filling, saves the operator's time and workload.

大容量墨盒，减少加墨频率，省时省力。



White Ink Circulation

White ink stirring motor and circulation system are equipped to avoid the white ink sediment, reduce the machine wear and tear, and extend the service life.

白墨搅拌和循环系统，避免白墨沉淀影响喷头寿命。

• Specification 参数表

Model 型号	Nova 60	
Printing width 打印宽度	70cm	
Print head 喷头型号	XP600/4720/i3200	
Print head qty. (pc) 喷头数	2pcs	
Suitable media 介质	PET film	
Heating and drying function 加热烘干功能	Front guide plate heating, solidified upper drying, and cold air cooling function 前导板加热、上烘干固化、冷风降温	
Printing speed 打印速度	XP600 2 print heads 6pass 5m2/h 8pass 3m2/h	4720/i3200 2 print heads 6pass 8m2/h 8pass 6m2/h
Printing resolution 打印精度	720dpi/1080dpi/1440dpi/2880dpi	
Print head cleaning 喷头清洗	Automatic 自动	
Heating method 加热方式	Front guide plate heating (30°C~65°C) 前导板加热	
Platform suction adjustment 平台吸风调节	Available 已配置	
Printing interface 数据传输	USB3.0	
Working environment 工作环境	Temperature 15~30°C	
Relative humidity 相对湿度	40%-60%	
Software 软件	Maintop/PhotoPrint 蒙泰、PP	
Operating system 操作系统	Window XP/Window 7/Window 10	
Rewinding function 收纸	Automatic induction rewinding 自动感应收纸	
Rated power 功耗	250±5%W	
Machine size 机器尺寸	打印机 Nova 60 printer: 163*78*130cm	
	抖粉机 Powder shaker and dryer: 209*109*108cm	
Packaging Size 包装尺寸	打印机 Nova 60 printer: 197*75*69cm, 93kg	
	抖粉机 Powder shaker and dryer: 193*112*113cm, 60kg	