

Direct to / T恤打印机 Garment Printer

RB-4030T RB-4060T

Color the world


- 2 pcs of printheads 双喷头
- Auto height detection 自动测高
- 40*30cm/40*60cm print size A3/A2打印尺寸
- Color-White in one pass 白彩同打



Direct to / T恤打印机 Garment Printer

4030/4060 DTG

• Features 特点



Solid Linear Guideways

It is equipped with straight square rail on XYZ axis, which makes printing smoother and machine lifespan longer.

XY轴配备直方导轨，打印更流畅，机器寿命更长。



Touch Panel

6 inches touch screen with necessary functions, make the printing even more convenient.


6英寸触摸屏，具备所有必要的功能，使打印更加方便。



Inspection Windows

4 openable windows for easier troubleshooting without disassembling the machine.

4个可打开窗口，无需完全打开机盖即可轻松排除故障。



White Ink stirring

The white ink circulation system avoids the precipitation. In addition, it is equipped with an ink shortage alarm system.


白墨搅拌系统避免白墨沉淀，另外配有缺墨报警器。



Strong Cooling System

Powerful cooling fans for main board+water circulation system for UV LED lamps ensure stable and operation time.

强力风冷+分体水冷，确保机器长期稳定运行。



Upgraded driving method

Upgrade to rack from the lead screw, which increases the load capacity, stability, and speed.

从丝杠升级到机架，提高了负载能力、稳定性和速度。

• Application 打印案例



• Specification 参数表

Name		RB4030T	RB-4060T
Printhead 喷头		Double XP600/4720 Print Heads	
Resolution 分辨率		720*720dpi, 40*30cm/40*60cm size	
Ink 墨水	Type 类型	Textile pigment ink纺织墨水	
	Package size 包装	500ml per bottle 500ml每瓶	
	Ink supply system 墨路系统	CISS(500ml ink tank)连续供墨系统	
	Consumption 消耗量	9-15ml/sqm	
Ink stirring system 白墨搅拌	Available		
Maximum printable area(W*D*H) 打印区域	Horizontal 平面	40*30cm(16*12inch;A2)	40*60cm(16*25inch ,A3)
	Vertical 垂直	Substrate 15cm(6inches) /rotary 8cm(3inches)	
Media 介质	Type 类型	Cotton,Nylon,30%Polyester,Canvas,Jute,Odile Cotton, Velvet, Bamboo Fiver, Wool Fabric etc 棉、尼龙、30%涤纶、帆布、黄麻、Odile 棉、天鹅绒、竹纤维、羊毛织物等	
	Weight 重量	≤15kg	
	Media (object) holding method 平台类型	Glass Table(standard)/Vacuum table(optional) 默认玻璃平台，可升级金属真空吸附平台	
Software 软件	RIP图像处理软件	Maintop 6.0 or PhotoPrint DX Plus	
	Control控制软件	Wellprint	
	Format可接受格式	.tif/.jpg/.bmp/.gif/.tga/.psd/.psb/.ps/.eps/.pdf/.dcs/.ai/.eps/.svg	
	System操作系统	Window XP/ Windows 7/ Window 10	
	Interface数据接口	USB2.0/3.0 Port	
Power 电力	Language 语言	Chinese/English	
	Requirement 电力要求	50/60HZ 220V(±10%) < 5A	
Dimension 尺寸	Consumption 功耗	800W	
	Assembled 机器尺寸	97*101*56cm	63*101*56cm
	Operational 建议操作空间大小	118*116*76cm	119*83*73cm
Weight 重量		net 90kg/ Gross 140kg	net 70kg/ Gross 101kg